

低温截止阀

● DJ41Y/F



主要连接尺寸及外形尺寸

单位:mm

DN	L	D	D1	D2	b	D0	Z-Φd	-46°C	-101°C	-196°C
DJ41Y-16C DJ41Y-16P DJ41Y-16R DJ641Y-16C DJ641Y-16P DJ641Y-16R DJ9B51Y-16C DJ9B41Y-16P DJ9B41Y-16R										
50	230	160	125	100	16	4-Φ18	240	460	480	520
65	290	180	145	120	18	4-Φ18	280	475	505	525
80	310	195	160	135	20	8-Φ18	280	520	550	590
100	350	215	180	155	20	8-Φ18	320	545	575	615
125	400	246	210	185	22	8-Φ18	360	590	620	660
150	480	280	240	210	24	8-Φ23	400	650	680	730
200	600	335	295	265	26	12-Φ23	400	850	880	930
250	730	405	355	320	30	12-Φ25	450	956	986	1036
300	850	460	410	375	30	12-Φ25	500	1095	1125	1175
DJ41Y-25 DJ41Y-25P DJ41Y-16R DJ641Y-25C DJ641Y-25P DJ641Y-25R DJ9B51Y-25C DJ9B41Y-25P DJ9B41Y-25R										
50	230	160	125	100	20	4-Φ18	240	460	480	520
65	290	180	145	120	22	8-Φ18	280	475	505	525
80	310	195	160	135	22	8-Φ18	280	520	550	590
100	350	230	190	160	24	8-Φ23	320	545	575	615
125	400	270	220	188	28	8-Φ25	360	590	620	660
150	480	300	250	218	30	8-Φ25	400	650	680	730
200	600	360	310	278	34	12-Φ25	400	850	880	930
250	730	425	370	332	36	12-Φ30	450	956	986	1036
300	850	485	430	390	40	16-Φ30	500	1095	1125	1175
DJ41Y-40 DJ41Y-40P DJ41Y-40R DJ641Y-40C DJ641Y-40P DJ641Y-40R DJ9B51Y-40C DJ9B41Y-40P DJ9B41Y-40R										
50	230	160	125	100	88	20	240	483	504	546
65	290	180	145	120	110	22	280	499	530	551
80	310	195	160	135	21	22	280	546	578	620
100	350	230	190	160	150	24	320	572	604	646
125	400	270	220	188	176	28	360	620	651	693
150	480	300	250	218	204	30	400	683	741	767
200	600	360	320	282	260	38	400	893	924	977
250	730	425	385	345	313	42	450	1004	1035	1088
300	850	485	450	408	364	46	500	1150	1181	1234